

## Regina Forklift Training Course

Regina Forklift Training Course - CSA and OSHA establish criteria for forklift safety training that meets current standards and regulations. Anyone planning to utilize a forklift is needed to successfully complete safety training before utilizing whatever type of forklift. The accredited Forklift Operator Training Program is intended to provide trainees with the practical skills and knowledge to become a forklift operator.

Mobile Equipment and Vehicle safety rules that apply to forklift utilization involve pre-shift checks, and regulations for lifting and loading.

An inspection checklist should be carried out and submitted to the supervising authority before beginning a shift. When a maintenance problem is uncovered, the utilization of the particular equipment should be stopped until the issue has been addressed. To be able to indicate the machine is out of order, the keys must be removed from the ignition and a warning tag placed in a visible place.

Safety rules for loading will comprise checking the load rating capacity on the forklift to determine how much the equipment could handle. When starting the machine, the forks must be in the down position. Bear in mind that there is a loss of around one hundred pounds carrying capacity for every inch further away from the carriage which the load is carried.

Lifting must begin with the driver moving to a stopped position approximately three inches from the load. The mast should then be leveled until it has reached a right angle with the load. Lift the forks to one inch beneath the slot on the pallet and drive forward. Then lift forks four inches. Tilt back the load to secure it for moving. Drive the lift backwards if the load obscures frontal vision. Check behind and honk in order to alert other staff. Never allow forks to drag on the ground.

The load must be loaded by the forklift in such a way that ensures the load is secure and will not create a hazard to other people or objects. Restraining loads is required for materials which may shift during transport and destabilize the forklift.

To be able to avoid the movement of drums, drums could be strapped together to decrease movement. Forklift operators must drive slowly when moving liquids, to lessen instability in the forklift.