Regina Scissor Lift License

Regina Scissor Lift License - The operation of scissor lifts carries an inherent risk of danger. Whichever kind of powered equipment needs proper handling to be able to avoid accidents causing damage or injury. Companies should ensure that personnel utilizing this particular machine have the needed training.

Companies should not permit scissor lifts to be utilized by untrained people. The scissor lift is used to lift people to high levels. Failure to know and fully abide by safety standard could lead to damage to the lift or injuries for users.

There are no regulations governing the utilization of fall protection for those who use scissor lifts. However, manufacturers may recommend the utilization of fall protection and in several situations tying off in scissor lifts might be required by employer rules, job-specific risk assessments or local rules.

Prior to using the machine, the scissor-lift operator has to carry out a thorough inspection to be able to ensure the equipment is in good working order. This is the operator's job, even though the unit has already been in service that very same day. The operator's guidebook of the equipment contains a pre-operation checklist.

Examples of what to look for when doing a pre-operation inspection comprise checking tire-inflation pressure, and checking controls in the platform and ground controls in order to make certain they are working. When extending or retracting the boom, watch for delayed movement on the fly section that could indicate loose cables. While operating the controls, make certain that the emergency stop switches are working. Operate functions against the equipment's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters must automatically stop the unit before it moves into an unstable position, if they are functioning right. If they aren't, turn off the lift and ensure that repairs are made before utilizing it for a second time.

Safe operating procedures must be followed always, with the levers being operated with even, controlled pressure. A control lever should never be pushed from one position to the opposite position. The lever should be shifted to neutral, prior to stopping, and then proceeding in the desired direction. When released, control switches and levers should return to the neutral position automatically. Depress the foot switch prior to operating platform controls.